



SOLE-sys 1306 Mifare Validatör GPRS

Technical specifications:

Model:	SOLE-1306 bus pos terminal
Dimension:	200*151*61.5mm
Material:	Engineering Plastics, Anti static electricity coating design, be protected from high-frequency interference
Display:	3.5 inch LCD display, 320x240
Operating system:	Linux 2.6 system
CPU:	N32905 processor, ARM9 core @ 240MHZ
Memory:	32MBytes SDRAM, 128MB NANDFlash
Data capacity:	259840 pcs of detailed data for console storage, unlimited data at GPRS storage
Card capacity:	91,880,000 pcs
Black list:	91,880,000 pcs (download thru PC with USB)
Working Voltage:	DC 8V-50V
Operating temperature:	-40°C~75°C
Storage temperature:	-45°C~85°C
Humidity:	0-95% RH non condensing
Lighting:	Red, Green light
Sound prompt:	Buzzer, single channel speaker (voice report)
Voice report prompt:	16KHz,16bit single channel voice report prompt
Keypad:	4 command buttons
RFID:	Can read and write ISO14443 TYPE A\B Electronic tag (Incl. Combi-Card)
Read card distance:	0~50mm
Supporting card:	Mifare 1 card, Mifare DESfiire card,CPU card, UnionPay IC card

Frequency:	13.56MHz
Interfaces/Connectors:	RS232, RS485, USB
Printer modules:	Can be connected to slip printer-POS58
Width of receipt:	Based on printer configuration
Positioning mode:	GPS
Power consumption:	≤10W
Communication Modules:	GPRS(900Mhz/1800Mhz), or CDMA(800Mhz)
WIFI:	Supporting 802.11n/b/g standards,150Mbps,2.4Ghz
UnionPay:	Compatible for PBOC3.0 UnionPay card
Upgrading:	Connect USB to PC, upgrade with GPRS
Data collection:	WIFI, GPRS, USB

