



LINUX



SOLE-sys B0409 Yükleme Terminali

Technical specifications:

Dimension	: 217*83*46mm
Material	: Engineering Plastics, Anti static electricity coating design, be protected from high-frequency interference
Display	: 2.8 inch LCD display (320*240)
Operating system	: Linux 2.6 system
CPU	: N32905 processor, ARM9 core @ 240MHZ
Memory	: 32MBytes SDRAM, 128MB NANDFlash
Data capacity	: 259840 pcs of detailed data for console storage
Card capacity	: 91,880,000 pcs
Black list	: 91,880,000 pcs (download thru PC with USB)
Working Voltage	: DC12V
Battery	: 7.4V 2000mAh Li-polymer
Operating temperature:	-20°C~60°C
Storage temperature :	-40°C~85°C
Humidity	: 0-90% RH non condensing
Pilot lamp	: Red, Green, Yellow light
Sound prompting	: buzzer
Keypad	: In-built 24 pcs Alpha-numeric keypad
Flash Memory	: 64 Mbyte, can be extended to 256 Mbyte
RFID	: Can read and write ISO14443 TYPE A\B Electronic tag (Incl. Combi-Card)
Read card distance	: 0~50mm
Frequency	: 13.56MHz
Supporting card	: Mifare 1 card, Mifare DESfire EV1, CPU card, UnionPay IC card
Interfaces/Connectors:	RS232, USB
Printer	: in-built Thermal Printer

Width of receipt : Thermal paper, 58 x 30 mm
Power consumption : Static: ≤0.2 W; Dynamic: ≤15 W
Communication Modules: GPRS(900Mhz/1800Mhz), or CDMA(800Mhz)
WIFI : Supporting 802.11n/b/g standards,150Mbps,2.4Ghz
UnionPay : Compatible for PBOC3.0 unionpay card
Upgrading : Connect USB to PC, upgrade with GPRS
Data collection : WIFI, GPRS, USB

